archerwell.com

Tornar[®] Casing Scraper (Non-Rotating) Clean and solids-free wellbore

conditions.

without rotation.

Tornar[®] Casing Scraper is a mechanical tool for cleaning and polishes the casing or liner ID to remove mud solids, cement sheath, scale and perforation burrs in any wellbore.



The Tornar[®] Casing Scraper can be integrated as a

during the displacement process prior to running

without fear of damage to casing or tool due to the

external bolts that could work loose under extreme

A Tornar® Casing Scraper tool consists of a onepiece

Body, non-rotating Stabiliser and Scraper assembly.

Scraper assembly to avoid wear or damage to the

The Scraper assembly is self-centralising inside the

conditions. It's also rough, flexible and has the force

casing or liner to ensure equal cleaning at all well

needed remove and clean 360 degrees

casing during drill string rotation.

The main mandrel rotates through the stabiliser and

rugged design and the fact that it doesn't contain

completion. It can be rotated and reciprocated

part of a complete wellbore cleaning tool string used

Benefits

- Clean 360 degrees without rotation
- Eliminates casing wear
- High strength mandrel
- Simple to run
- Multiple run possible
- Withstand drilling and milling operations
 Suitable for HP wells and can withstand
- chemical or acid attack

Applications

- Cleaning debris from wellbores in any wellbore cleanup operations
- Post perforation cleaning
- Cleaning after side track operations
- When cleaning is required in drilling operations

Features

- One piece mandrel
- Non rotating stabilizers
- Non rotating scraper sleeve
- No external nuts or bolts
- Standard drill pipe connections
 Extra Large bypass areas for eliminating flow restrictions

Specifications

-	
Casing sizes	4 1/2" to 14"
Thread	API and Premium
ID	1 3/4" to 4"
Maximum rotation speed	150 rpm
Working temperature	150°C / 302°F
Max. trip speed in casing	Limited by rig equipment
Max. pump rate	Limited only by surface equipment
Material (main body)	AISI 4145M 110 KSI
Burst pressure	690 bar - 10 000 psi

Specifications may be subject to change

Archer is a global oil services company with a heritage that stretches back over 40 years. With a strong focus on safety and delivering the highest quality products and services, Archer operates in 40 locations over 19 countries providing drilling services, well integrity & intervention, plug & abandonment and decommissioning to its upstream oil and gas clients. **We are Archer**.



