

Tornar® String Magnet (Non-Rotating)

Clean and solids-free wellbore

Tornar® String Magnet is a mechanical tool that collects metallic debris in the casing or liner IDs from any wellbore. It is designed to capture a large volume of metallic debris while maintaining large flow volumes.



TORNAR®

Benefits

- Large debris capacity
- High strength single pole magnets
- Eliminates casing wear
- High strength mandrel
- Simple to run
- Multiple run possible
- Withstand drilling and milling operations

Typical applications

- Cleaning debris from wellbores in any wellbore cleanup operations
- Post perforation cleaning
- Cleaning after side track operations
- When cleaning is required in drilling operations
- In combination with BOP and riser cleaning
- Allows running in combination with any LOCK® Plug for BOP testing, pipe hang off and well cleaning

Features

- One piece mandrel
- Non rotating stabilizers
- Non rotating magnet sleeve
- No external nuts or bolts
- Extra Large bypass areas for eliminating flow restrictions
- Fluted spiral stabilizer sleeves for generous fluid and debris bypass

The Tornar® String Magnet can be integrated as a part of a complete wellbore cleaning tool string during the displacement process prior to running completion. It can be rotated and reciprocated without damaging the casing or tool. This is due to its rugged design and the fact that it does not contain external bolts that could become loose under extreme conditions.

As the Tornar® String Magnet is run in hole the high capacity magnets remove debris from the casing ID and drilling fluid. The non-rotating stabilizers on the Tornar® String Magnet provide a standoff as well as a generous flow area for fluid by-pass around the tool. The non-rotating stabilizers also reduce any possible casing wear. The non-rotation magnet sleeve ensures no debris is washed away during rotation. Rotation up to 150 rpm may be applied to create turbulent flow and remove cutting bed.

The Tornar® String Magnet should be run when significant ferrous debris may potentially exist.

Specifications

| | |
|---------------------------|-----------------------------------|
| Casing/liner sizes | 4 1/2" to 14" |
| Thread | API and Premium |
| ID | 1 3/4" to 4" |
| Maximum rotation speed | 150 rpm |
| Working temperature | 150°C / 302°F |
| Max. trip speed in casing | Limited by rig equipment |
| Max. pump rate | Limited only by surface equipment |
| Material (main body) | AISI 4145M 110 KSI |
| Burst pressure | 690 bar - 10 000 psi |
| Debris capacity | Up to 94 kg / 207 lbs |
| Magnet force | Up to 1850 kg |

Specifications may be subject to change



Archer is a global oil services company with a heritage that stretches back over 40 years. With a strong focus on safety and delivering the highest quality products and services, Archer operates in 40 locations over 19 countries providing drilling services, well integrity & intervention, plug & abandonment and decommissioning to its upstream oil and gas clients. **We are Archer.**