

TIMELOCK™

with Drag Block Cover

The **TIMELOCK™ Plug with Drag Block Cover** is a plug specifically designed to allow retrieval without interference with the wear bushing.

The plug is installed as a barrier as a standard LOCK® plug, but after releasing the plug a ball is dropped and pressure is applied in order to push a cover over the Drag Blocks. This will collapse the Drag Blocks to prevent them from catching and retrieving the wear bushing when POOH.

Benefits

- Saves Operational time
- Saves Operational cost
- Reduces rig site handling
- Improving safety standards

Features

- ISO 14310 certified, VO
- No set weight needed below
- High differential pressure elements
- Unrestricted, slick OD upon retrieval

Specifications

Setting range (in)	12,250- 12,529
Pressure rating, psi (bar)	6,090 [420]
Temperature rating, °F [°C]	39 – 266 [4 – 130]
ISO 14310 qualification	VO
Max Hang-off weight, k lbs [tons]	154 [70]

Specifications may be subject to change and other sizes may be available on request



Archer is a global oil services company with a heritage that stretches back over 40 years. With a strong focus on safety and delivering the highest quality products and services, Archer operates in 40 locations over 19 countries providing drilling services, well integrity & intervention, plug & abandonment and decommissioning to its upstream oil and gas clients. **We are Archer.**